



BEARING DRIVESHAFT ANDERSON, INC.



45 mm x 75 mm x 16 mm SNR
MLE7009HVUJ74S Angular contact ball bearing

Bearing No. MLE7009HVUJ74S

MLE7009HVUJ74S Bearing 2D drawings and 3D CAD models

Size	45x75x16 mm
Bore Diameter	45 mm
Outer Diameter	75 mm
Width	16 mm
d	45 mm
D	75 mm
B	16 mm
C	16 mm
Angle (°)	20 °
d1	54.7 mm
d2	52.4 mm
D1	66.31 mm
D2	68.46 mm
a	22 mm
Contact angle	25 °
rs min	1 mm
r1s min	0.6 mm
f0	8.34
Precision class	P4S
Mass	0.24 kg
Dynamic load, C	10.3 kN
Static load, C0	6.7 kN
Fatigue limit load, Cu	0.4 kN
Nlim (grease)	23,000 rpm
Axial displacement K Factor	0.68



BEARING DRIVESHAFT ANDERSON, INC.

Preload level	7
Preload value	0.09 kN
Axial rigidity	92 N/ μ m
Radial rigidity	205 N/ μ m
Min operating temperature, T _{min}	-20 ° C
Max operating temperature, T _{max}	120 ° C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.17 Hz
Characteristic outer ring frequency, BPF0	9.92 Hz
Characteristic inner ring frequency, BRFI	12.08 Hz
da min	50.5 mm
db min	50.5 mm
Da max	69.5 mm
Db max	69.5 mm
r1a max	0.6 mm
ra max	1 mm
D6	56.9 mm